

Data sheet for LT XLPE Cable

| S.No | Particulars | 4 X 6 |
|------|---|--|
| 1 | Name of Manufacturer | Polycab Wires Pvt. Ltd, Daman |
| 2 | Item Code | PISLV4X610690 |
| 3 | Type of cable | 2XWY |
| 4 | Voltage Grade V | 1100 |
| 5 | No of cores X size in sqmm | 4 X 6 |
| 6 | Conductor | |
| a) | Material | Plain annealed Copper as per Class 1 of IS:8130/84 |
| b) | Max. d.c. resistance of conductor at 20° C (ohm/km) | 3.08 |
| c) | Shape of the conductor | Solid Circular |
| 7 | Insulation | |
| a) | Material | XLPE as per IS 7098(Pt-1)/88, Latest |
| b) | Nominal thickness (mm) | 0.7 |
| 8 | Inner Sheath | |
| a) | Material | Extruded PVC Type ST2 as per IS:5831/84 |
| b) | Minimum thickness (mm) | 0.3 |
| 9 | Armouring | |
| a) | Material | Galvanised Steel |
| b) | Type of armouring | Round Wire |
| c) | Nominal size of armour (mm) | 1.40 |
| 10 | Outer Sheath | |
| a) | Material | PVC Type 'ST2' as per IS:5831/84 |
| b) | Thickness (mm) | 1.24 (Min.) |
| 11 | Electrical Parameters | |
| a) | Max. a.c. resistance of conductor at 90° C (ohm/km) | 3.93 |
| b) | Calculated Cable reactance (ohm/km) | 0.0869 |
| c) | Impedance of cable (ohm/km) | 3.93 |
| d) | Approx. Cable Capacitance (mfd/km) | 0.26 |
| 12 | Maximum conductor temperature under normal operating conditions | 90°C |
| 13 | Maximum conductor temperature at the termination of short circuit | 250°C |
| 14 | Short Circuit rating of conductor for the duration of 1 sec (kA) | 0.86 |



POLYCAB WIRES PVT. LTD.

Polycab House, 771, Mogul Lane, Mahim (W), Mumbai 400 016, India.
Tel.: +91 22 2432 7070-74 | Fax: +91 22 2432 7075 | Email: bdg@polycab.com | www.polycab.com



| | | |
|------|--|--|
| 15 | Continuous Current carrying capacities :- | |
| (a) | In Ground at 30°C (A) | 56 |
| (b) | In Air at 40°C (A) | 52 |
| 16 | Applicable Standard | IS 8130/84, IS 7098 Part I/88, IS 5831/84, IS 3975/88 etc. with latest up to date amendments |
| 17 | Approx. overall diameter of the cable in mm | 17.0 ± 2.0 |
| 18 | Minimum bending radius | 12 times Overall diameter |
| 19 | Max. Tensile strength | |
| (i) | for Cables pulled with stocking (Newtons) | 9 x D ² , D is the cable OD in mm |
| (ii) | for Cables pulled with pulling eyes (N) | 1,200 |
| 20 | Colour of outer sheath. | Black |

Note:-The values given above are subject to tolerances as per the relevant standards.



India's No.1 Cable & Wires Company



Works - Daman:
52/5-8, Daman Industrial Estate,
Village Kadaiya, Daman - 396210.
Tel : (0260) 3091031/070, 2220422 /425/428
Fax : (0260) 2221009

Works - Halol:
Unit 4, Plot No. 67-72, Nurpura,
Taluka - Halol, District Panchmahal,
Gujarat 389350.
Tel: 02676 320862/326801