

**Data sheet for LT XLPE Cable**

S.No	Particulars	3.5 X 300
1	Name of Manufacturer	Polycab Wires Pvt. Ltd, Daman
2	Item Code	SISLV3.5X30017733
3	Type of cable	A2XFY
4	Voltage Grade V	1100
5	No of cores X size in sqmm	3.5 X 300
6	<b>Conductor</b>	
a)	Material	H2/H4 Grade Aluminium as per Class 2 of IS: 8130/84,latest
b)	Max. d.c. resistance of conductor at 20° C (ohm/km)	
	Main	0.100
	Neutral	0.206
c)	Shape of the conductor	Stranded Compacted Sector
7	<b>Insulation</b>	
a)	Material	XLPE as per IS 7098(Pt-1)/88, Latest
b)	Nominal thickness (mm)	
	Main	1.8
	Neutral	1.4
8	<b>Inner Sheath</b>	
a)	Material	Extruded PVC Type ST2 as per IS:5831/84
b)	Minimum thickness (mm)	0.6
9	<b>Armouring</b>	
a)	Material	Galvanised Steel
b)	Type of armouring	Flat Strip
c)	Nominal size of armour (mm)	4.0 x 0.8
10	<b>Outer Sheath</b>	
a)	Material	<b>FRLS</b> PVC Type 'ST2' as per IS:5831/84
b)	Thickness (mm)	2.20 (Min.)
11	<b>Electrical Parameters</b>	
a)	Max. a.c. resistance of conductor at 90° C (ohm/km)	0.130
b)	Calculated Cable reactance (ohm/km)	0.0703
c)	Impedance of cable (ohm/km)	0.148
d)	Approx. Cable Capacitance (mfd/km)	0.71
12	Maximum conductor temperature under normal operating conditions	90°C
13	Maximum conductor temperature at the termination of short circuit	250°C
14	Short Circuit rating of conductor for the duration of 1 sec (kA)	28.35



**POLYCAB WIRES PVT. LTD.**

Polycab House, 771, Mogul Lane, Mahim (W), Mumbai 400 016, India.  
 Tel.: +91 22 2432 7070-74 | Fax: +91 22 2432 7075 | Email: bdg@polycab.com | www.polycab.com



15	<b>Continuous Current carrying capacities :-</b>	
(a)	In Ground at 30°C (A)	369
(b)	In Air at 40°C (A)	452
16	Applicable Standard	IS 8130/84, IS 7098 Part I/88, IS 5831/84, IS 3975/88 etc. with latest up to date amendments
17	Approx. overall diameter of the cable in mm	58.5 ± 2.0
18	Minimum bending radius	12 times Overall diameter
19	Max. Tensile strength	
(i)	for Cables pulled with stocking (Newtons)	9 x D <sup>2</sup> , D is the cable OD in mm
(ii)	for Cables pulled with pulling eyes (N)	31,500
20	Colour of outer sheath.	Black

Note:-The values given above are subject to tolerances as per the relevant standards.



India's No.1 Cable & Wires Company



Works - Daman:  
 52/5-8, Daman Industrial Estate,  
 Village Kadaiya, Daman – 396210.  
 Tel : (0260) 3091031/070, 2220422 /425/428  
 Fax : (0260) 2221009

Works - Halol:  
 Unit 4, Plot No. 67-72, Nurpura,  
 Taluka – Halol, District Panchmahal,  
 Gujarat 389350.  
 Tel: 02676 320862/326801